





TEST REPORT IES LM-79-08

TÜV SÜD Test Report for Electrical and Photometric Measurements of Solid-State Lighting Products

Report reference No.	70.402.17.014.42-09
Date of issue	2018-09-01
Project handler	Mr. Kaishuang LI
Testing laboratory	TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
Address	No. 151 Hengtong Road, 200070, Shanghai, P.R.China.
Testing procedure	<input type="checkbox"/> TMP <input type="checkbox"/> WMTL <input type="checkbox"/> SMTL <input type="checkbox"/> LTR
Testing location	No. 1999, Duhui Road, Shanghai, 201108, P. R. China
Client	Everlite LED Lighting Co., Limited
Client number	91783
Address	Room 2105, Trend Centre, 29-31, Cheung Lee Street, Chaiwan, Hong Kong
Contact person	Jackie ZHANG
Standard	This TÜV SÜD test program is based on the following requirements: IES LM-79-08
TRF originated by	TÜV SÜD Product Service GmbH, Mr. Kenneth Lau
Copyright blank test report	This test report is based on the content of the standard (see above). The test report considered selected clauses of the a.m. standard(s) and experience gained with product testing. It was prepared by TÜV SÜD Product Service GmbH. TUV SUD Group takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.
Test procedure	<input type="checkbox"/> TÜV Mark <input checked="" type="checkbox"/> without certification
Non-standard test method	N/A
National deviations	N/A
Number of pages (Report)	18
Number of pages (Attachments)	N/A
Compiled by	Approved by
(+ signature)  Mr. Kaishuang LI	(+ signature)  Ms. Lucy LU



Test sample	LED Luminaire (LED Street Light)	
Type of test object	Fixed	
Trade mark	N/A	
Model and/or type reference	EL-SL18MA-60W-4000K	
Lens type	TYPE II	
Rating(s)	220-240V AC, 50/60Hz, 60W, Class II, IP66	
Manufacturer	Ningbo Shishang Photoelectricity Technology Co., Ltd.	
Manufacturer number	92974	
Address	No.19, KeSan Road, Ninghai, 315600, Ningbo, Zhejiang, People's Republic of China	
Sub-contractors/ tests (clause)	N/A	
Name	N/A	
Order description	<input type="checkbox"/>	Complete test according to TRF
	<input checked="" type="checkbox"/>	Partial test according to manufacturer's specifications
	<input type="checkbox"/>	Preliminary test
	<input type="checkbox"/>	Spot check
	<input type="checkbox"/>	Other:
Date of order	2017-12-29	
Date of receipt of test item	2018-08-27	
Date(s) of performance of test	2018-09-01	
Test item particulars (delared):		
Lamp type :	<input type="checkbox"/> Bare lamp <input type="checkbox"/> Covered lamp, no reflector <input type="checkbox"/> Lamp with reflector <input checked="" type="checkbox"/> other: LED Street Light	
Lamp cap installed :	N/A	
Rated Votage (V) :	220-240	
Rated Power (W) :	60	
Rated Power Factor :	N/A	
Rated Luminous Flux (lm) :	N/A	
Rated CCT (K) :	4000	
Rated CRI :	N/A	



Attachments:

1. Test Equipment List

General remarks:

"(see remark #)" refers to a remark appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a comma is used as the decimal separator.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

Summary of testing:

☐ deviation(s) found

☒ no deviations found

The test was operated at 230V, 50Hz, in accordance with the applicant's instruction.

Model	Luminous Efficacy (Lumens/Watt)	Total Luminous Flux (Lumens)	Input Power (Watts)
EL-SL18MA-60W-4000K	148,38	9110,3	61,40
Power Factor	CCT (K)	CRI	Stabilisation Time (minutes)
0,9755	3995	72,2	90

Copy of marking plate:

Not provide

Picture of the product:



Characteristic data

Dimension (mm, Height x Width x Length): 249mm*273mm*675mm

Weight: approximately : 6,8Kg

Purpose of the product

LED Street light for generally lighting purpose.

Possible test case verdicts:

- test case does not apply to the test object:: N(A.) / not included in the order
- test object does meet the requirement.....: P(ass)
- test object does not meet the requirement:: F(ail)

Possible suffixes to the verdicts:

- suffix for detailed information for the client.....: - C(omment)
- suffix for important information for factory inspection...: - M(anufacturing)

Clause	Requirement	Test	Measuring result	Remark	Verdict
2.0	Ambient Conditions				P
2.1	General				P
2.2	Air Temperature				P
2.3	Thermal Condition for Mounting SSL Products				P
2.4	Air Movement				P
3.0	Power Supply Characteristics				P
3.1	Waveshape of AC power supply				P
3.2	Voltage regulation				P
4.0	Seasoning of SSL Product		No seasoning of SSL product		P
5.0	Stabilisation of SSL Product		Sufficiently stabilised before measurement		P
6.0	Operation Orientation				P
	SSL product shall be stabilized and measured in intended operating orientation				P
7.0	Electrical Settings				P
	SSL product shall be operated at rated voltage				P
	SSL product with dimming capability are tested at maximum input power condition				N/A
	SSL product with different modes are measured in all relevant modes				N/A
8.0	Electrical Instrumentations				P
8.1	Circuits				P
8.2	Uncertainties				P
9.0	Test methods for Luminous Flux measurement				P
9.1	Integrating sphere with a spectroradiometer (Sphere-spectroradiometer system)				N/A
9.2	Integrating sphere with a photometer head (Sphere-photometer system)				N/A
9.3	Goniophotometer				P
10.0	Luminous Intensity Distribution				P
	Reporting acc. to IEC LM-63		See table 3		P
11.0	Luminous Efficacy		See table 1		P
12.0	Test Methods for Color Characteristics of SSL Products				P
	Measurements		See table 1		P
13.0	Uncertainty statement				P

Table 1	Test data		
Model	EL-SL18MA-60W-4000K		
Rated Voltage (V):	AC 220-240	Rated Power (W):	60
Rated luminous flux (lm):	N/A	Ambient temperature 25 ±1°C (°C):	25,3
Test item		Measured Value	
		Integrating Sphere	Goniophotometer
Key Photometric Results			
Luminous Efficacy (Lumens/Watt)	-	148,38	
Total Luminous Flux (Lumens)	-	9110,3	
Correlated Color Temperature (CCT)	3995	-	
Color Rendering Index (CRI)	72,2	-	
Chromaticity (Chroma x / Chroma y)	0,3826/0,3842	-	
Chromaticity (Chroma u / Chroma v)	-	-	
Chromaticity (Chroma u' / Chroma v')	0,2236/0,5052	-	
Duv Value	0,0028	-	
SDCM	1,60	-	
Color Angular Uniformity (Max. du'v')	-	-	
Stabilization Time (Light and Power) (Minutes)	90		
Total Run Time – Goniophotometer (Minutes)	150		
Spacing Criteria		C=15° / γ=1°	
Electrical Input Results			
Input Power (Watts)	-	61,40	
Input Voltage (Volts AC)	-	230,0	
Input Current (Amps)	-	0,2734	
Input Frequency (Hertz)	-	50,0	
Power Factor	-	0,9755	
A-THD (Current – Total Harmonic Distortion)	-	-	
Additional Information			
Ambient Temperature (°C):	25,3	25,3	
Photometric measurement condition	-	Photometric distance: 26m	
Number of hours operated prior to measurement	0h		
Orientation (burning position)	Base up, center of the Goniophotometer		
Supplementary Information:			
- Absorbtion Correction used: Yes			
Stabilisation was considered reached by: the variation (maximum-minimum) of at least 3 readings			
- of the light output and electrical power over a period of 30 minutes is less than 0.5%.			






Table 3		LIGHT DISTRIBUTION DIAGRAM			
Model:		EL-SL18MA-60W-4000K			
DATA OF LAMP		PHOTOMETRIC DATA Eff: 148.38 lm/W			
MODEL		I _{max} (cd)	4738	η street_up (%)	0.0
NOMINAL POWER (W)	60	LOR (%)	100	η street_down (%)	70.1
RATED VOLTAGE (V)		TOTAL FLUX (lm)	9110.3	η house_up (%)	0.0
NOMINAL FLUX (lm)	9110.3	MAXIMUM @ (C, γ)	30,38.0	η house_down (%)	29.7
LAMPS INSIDE	1	η up (%)	0.0	76 FLASHAREA (m2)	
TEST VOLTAGE (V)	230	η down (%)	100	SLI	

**INTENSITY DISTRIBUTION DIAGRAM
IN C PLANS**



UNIT: cd
— C0/180, 141.8deg
— C90/270, 56.3deg
AVERAGE BEAM ANGLE (50%): 99.1 DEG

**MAX INTENSITY CONE SURFACE
DISTRIBUTION DIAGRAM**




HOUSE SIDE Max @ γ = 38.0DEG STREET SIDE


Table 4a		LUMINOUS DISTRIBUTION INTENSITY DATA (unit: cd)							
Model:		EL-SL18MA-60W-4000K							
y \ C		0	15	30	45	60	75	90	105
0		1837.36	1837.36	1837.36	1837.36	1837.36	1837.36	1837.36	1837.36
5		2001.13	1990.91	1973.81	1949.28	1921.55	1888.58	1852.69	1818.35
10		2228.75	2210.33	2172.97	2119.36	2068.73	2015.52	1950.06	1876.74
15		2568.33	2532.24	2455.07	2359.36	2286.80	2225.27	2127.92	1989.81
20		2984.35	2925.66	2818.76	2683.69	2621.41	2559.11	2419.05	2181.34
25		3332.01	3284.70	3251.21	3227.51	3212.98	3073.00	2797.44	2369.78
30		3455.41	3420.52	3479.41	3667.67	3860.03	3686.94	3138.38	2463.59
35		3418.77	3421.44	3607.31	4027.68	4244.09	3984.10	3348.44	2476.59
40		3224.10	3287.95	3625.29	4232.39	4380.44	3815.80	3222.58	2431.73
45		2800.26	2933.29	3506.12	4275.95	4405.39	3944.48	3253.51	2378.44
50		2068.65	2267.17	3159.68	4197.37	4613.43	4165.16	3297.19	2238.95
55		1361.34	1452.63	2313.87	3926.97	4700.73	4298.03	3281.27	1992.94
60		794.73	806.99	1160.74	2983.16	4630.23	4212.95	3138.29	1621.88
65		340.64	362.19	402.82	1325.95	3826.73	3740.91	2539.82	1081.34
70		134.24	137.48	168.11	344.33	1585.23	2122.92	1183.94	434.91
75		91.52	83.93	89.19	152.82	515.50	766.94	346.39	182.72
80		33.67	36.75	33.48	56.54	184.52	165.61	66.55	39.81
85		0.65	0.69	1.56	5.14	6.55	3.64	1.87	1.18
90		0	0	0	0	0	0	0	0
95		0	0	0	0	0	0	0	0
100		0	0	0	0	0	0	0	0
105		0	0	0	0	0	0	0	0
110		0	0	0	0	0	0	0	0
115		0	0	0	0	0	0	0	0
120		0	0	0	0	0	0	0	0
125		0	0	0	0	0	0	0	0
130		0	0	0	0	0	0	0	0
135		0	0	0	0	0	0	0	0
140		0	0	0	0	0	0	0	0
145		0	0	0	0	0	0	0	0
150		0	0	0	0	0	0	0	0
155		0	0	0	0	0	0	0	0
160		0	0	0	0	0	0	0	0
165		0	0	0	0	0	0	0	0
170		0	0	0	0	0	0	0	0
175		0	0	0	0	0	0	0	0
180		0	0	0	0	0	0	0	0


Table 4b		LUMINOUS DISTRIBUTION INTENSITY DATA (unit: cd)							
Model:		EL-SL18MA-60W-4000K							
y \ C		120	135	150	165	180	195	210	225
0		1837.36	1837.36	1837.36	1837.36	1837.36	1837.36	1837.36	1837.36
5		1783.95	1752.55	1727.95	1714.49	1713.11	1724.09	1746.91	1781.51
10		1795.01	1710.05	1634.88	1588.30	1577.60	1602.43	1663.52	1752.46
15		1825.81	1668.21	1531.32	1448.27	1425.79	1463.58	1568.41	1731.79
20		1866.96	1569.35	1333.49	1199.63	1159.94	1211.57	1368.22	1639.89
25		1816.19	1365.33	1093.51	977.70	945.36	989.43	1135.76	1456.75
30		1744.76	1216.15	974.81	876.43	844.57	881.23	1008.72	1311.90
35		1713.35	1165.58	920.25	820.39	789.63	827.73	952.61	1263.77
40		1692.42	1157.89	884.64	771.68	740.36	780.44	920.11	1234.14
45		1623.69	1126.69	856.43	723.70	690.43	736.61	882.89	1177.73
50		1483.38	1063.37	810.40	676.47	642.30	691.76	829.29	1085.37
55		1273.02	942.25	731.03	600.58	562.10	613.39	739.87	945.12
60		1010.45	771.13	569.18	418.90	304.67	420.06	567.40	765.26
65		713.90	507.24	354.33	125.99	58.55	109.78	345.86	493.38
70		334.92	264.60	164.48	38.32	15.13	34.69	154.34	265.28
75		127.92	84.21	29.89	5.29	0.31	4.51	25.40	81.29
80		20.57	7.68	0.71	0.09	0.08	0.22	0.78	8.10
85		1.02	0.39	0.16	0.09	0.09	0.15	0.24	0.41
90		0	0	0	0	0	0	0	0
95		0	0	0	0	0	0	0	0
100		0	0	0	0	0	0	0	0
105		0	0	0	0	0	0	0	0
110		0	0	0	0	0	0	0	0
115		0	0	0	0	0	0	0	0
120		0	0	0	0	0	0	0	0
125		0	0	0	0	0	0	0	0
130		0	0	0	0	0	0	0	0
135		0	0	0	0	0	0	0	0
140		0	0	0	0	0	0	0	0
145		0	0	0	0	0	0	0	0
150		0	0	0	0	0	0	0	0
155		0	0	0	0	0	0	0	0
160		0	0	0	0	0	0	0	0
165		0	0	0	0	0	0	0	0
170		0	0	0	0	0	0	0	0
175		0	0	0	0	0	0	0	0
180		0	0	0	0	0	0	0	0

Table 4c		LUMINOUS DISTRIBUTION INTENSITY DATA (unit: cd)							
Model:		EL-SL18MA-60W-4000K							
y \ C	C	240	255	270	285	300	315	330	345
0		1837.36	1837.36	1837.36	1837.36	1837.36	1837.36	1837.36	1837.36
5		1817.82	1855.86	1897.40	1929.98	1957.87	1977.47	1994.95	2001.98
10		1851.17	1948.35	2042.33	2101.80	2145.46	2176.19	2206.53	2228.03
15		1931.85	2135.45	2311.96	2399.44	2443.67	2473.85	2518.84	2560.17
20		2009.23	2399.72	2730.25	2882.80	2921.74	2908.74	2962.24	2988.93
25		2004.67	2632.70	3137.16	3469.94	3663.64	3602.18	3478.01	3388.68
30		1955.39	2729.59	3429.00	4054.06	4331.39	4140.98	3783.32	3568.30
35		1897.53	2710.19	3584.41	4318.72	4680.97	4529.33	4007.20	3622.00
40		1830.96	2593.99	3405.95	4083.20	4708.89	4677.10	3995.50	3468.32
45		1709.24	2459.80	3319.61	4028.04	4566.00	4608.71	3847.46	3067.75
50		1524.39	2270.39	3304.72	4135.74	4665.00	4402.65	3431.06	2376.52
55		1284.51	1989.13	3229.64	4191.40	4718.70	4055.72	2467.38	1496.97
60		1005.66	1588.75	2999.21	4105.53	4580.84	3123.39	1178.61	809.35
65		714.75	1076.11	2376.82	3707.30	3853.48	1453.60	393.78	359.30
70		353.28	420.96	1004.25	2031.13	1865.25	320.87	167.79	137.30
75		125.97	182.06	299.50	667.61	624.41	181.95	94.11	84.86
80		22.12	39.10	53.67	135.66	233.21	74.74	37.49	37.82
85		1.02	1.71	2.07	5.54	13.29	8.55	2.67	0.98
90		0	0	0	0	0	0	0	0
95		0	0	0	0	0	0	0	0
100		0	0	0	0	0	0	0	0
105		0	0	0	0	0	0	0	0
110		0	0	0	0	0	0	0	0
115		0	0	0	0	0	0	0	0
120		0	0	0	0	0	0	0	0
125		0	0	0	0	0	0	0	0
130		0	0	0	0	0	0	0	0
135		0	0	0	0	0	0	0	0
140		0	0	0	0	0	0	0	0
145		0	0	0	0	0	0	0	0
150		0	0	0	0	0	0	0	0
155		0	0	0	0	0	0	0	0
160		0	0	0	0	0	0	0	0
165		0	0	0	0	0	0	0	0
170		0	0	0	0	0	0	0	0
175		0	0	0	0	0	0	0	0
180		0	0	0	0	0	0	0	0

Table 5		ZONAL FLUX DIAGRAM										
Model:		EL-SL18MA-60W-4000K										
γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lamp
10	2042	2176	2229	2119	1950	1710	1578	1752	0- 10	180.6	180.6	1.98
20	2730	2909	2984	2684	2419	1569	1160	1640	10- 20	597.2	777.8	8.52
30	3429	4141	3455	3668	3138	1216	844.6	1312	20- 30	1153	1931	21.1
40	3406	4677	3224	4232	3223	1158	740.4	1234	30- 40	1720	3651	40
50	3305	4403	2069	4197	3297	1063	642.3	1085	40- 50	2021	5672	62.1
60	2999	3123	794.7	2983	3138	771.1	304.7	765.3	50- 60	1959	7631	83.6
70	1004	320.9	134.2	344.3	1184	264.6	15.13	265.3	60- 70	1215	8846	96.9
80	53.67	74.74	33.67	56.54	66.55	7.676	0.0825	8.101	70- 80	251.4	9098	99.6
90	1.244	0.7611	0.2239	0.4911	1.177	0.6828	0.1656	0.5876	80- 90	12.82	9110	99.8
100	0	0	0	0	0	0	0	0	90-100	0.0428	9110	99.8
110	0	0	0	0	0	0	0	0	100-110	0	9110	99.8
120	0	0	0	0	0	0	0	0	110-120	0	9110	99.8
130	0	0	0	0	0	0	0	0	120-130	0	9110	99.8
140	0	0	0	0	0	0	0	0	130-140	0	9110	99.8
150	0	0	0	0	0	0	0	0	140-150	0	9110	99.8
160	0	0	0	0	0	0	0	0	150-160	0	9110	99.8
170	0	0	0	0	0	0	0	0	160-170	0	9110	99.8
180	0	0	0	0	0	0	0	0	170-180	0	9110	99.8
DEG	LUMINOUS INTENSITY:cd Less than 25% Percent = 7.1 %									UNIT:lm		











Table 10	LCS
Model:	EL-SL18MA-60W-4000K



The diagram is a circular IESNA luminaire flux distribution plot. It features concentric circles representing lumens at intervals of 900, from 900 to 4500. Radial lines indicate beam angles from 0 to 100 degrees. The plot is divided into zones: Front (0-90°), Back (90-180°), and Uplight (180-270°). The Front zone is further divided into Low (0-30°), Medium (30-60°), High (60-80°), and Very High (80-90°). The Back zone is similarly divided. The Uplight zone is divided into Low (90-100°) and High (100-180°). The diagram shows a primary beam of light directed towards the Front-Medium zone, with a smaller beam directed towards the Back-Medium zone. The Uplight zone shows minimal light distribution.

IESNA Luminaire Flux Distribution Table:		
Zone	Lumens	Luminaire %
FL - Front-Low(0-30)	1223.7	13.4
FM - Front-Medium(30-60)	4093.1	44.9
FH - Front-High(60-80)	1071	11.8
FVH - Front-Very High(80-90)	11.289	0.1
Total Forward Light	6399	70.2

BL - Back-Low(0-30)	707.5	7.8
BM - Back-Medium(30-60)	1607.1	17.6
BH - Back-High(60-80)	395.25	4.3
BVH - Back-Very High(80-90)	1.5301	0.0
Total Back Light	2711.4	29.8

UL - Uplight-Low(90-100)	0.042796	0.0
UH - Uplight-High(100-180)	0	0.0
Total Up Light	0.042796	0.0

BUG(Back,Up,Glare) Rating	B2-U0-G1
---------------------------	----------

Zone	Downward Lumens	Upward Lumens	Total Lumens
House Side	6399	0.017705	6399
Street Side	2711.3	0.025091	2711.4

Attachment 1: Equipment List

No.	Type	Manufacture	Model	Equipment ID	Next Calibration
1	Full-field Speed Goniophotometer	Everfine	GO-R5000	S1207714-YQ	May. 18.2019
2	High-accuracy Digital Photometer Head	Everfine	ID-1000_P-B/ID-1000_P-C	S1207714a-YQ	May. 18.2019
3	High-accuracy Digital Photometer Head	Everfine	ID-1000_P-B/ID-1000_P-C	S1207714b-YQ	May. 18.2019
4	High Accuracy Array Spectroradio Meter	Labsphere	CDS-600	S1312826-YQ	May. 18.2019
5	Standard Light Source	Everfine	D908	S1207714d-YQ	May. 18.2019
6	Digital Power Meter	Yokogawa	WT310	S1310805-YQ	May. 18.2019
7	Digital CC & CV DC Power Supply	Everfine	WY12010	S1207714f-YQ	May. 18.2019
8	Intelligent AC Power Source	Everfine	DPS1060	S1207714g-YQ	May. 18.2019
10	DC Power Supply	Everfine	WY3010	S1108624-YQ	May. 18.2019
11	Flux Reference Lamp	Labsphere	SCL-1400	S1602991-YQ	May. 18.2019
12	luminance Source	Everfine	SLS-150	S1108626-YQ	May. 18.2019
13	Thermometer	Fluke	Fluke 52-II	S0712414-YQ	May. 18.2019

-- END OF TEST REPORT --